

ATMOCE

Data Sheet

MI Series Microinverter

MI-1250/MI-1200/MI-1000/MI-900/MI-800



We reserve the right to modify product specifications without notice. While efforts are made to ensure accuracy, this material does not constitute any direct or implied commitment, warranty, or guarantee by ATMOCE. All information is provided "asis" and we disclaim liability for any reliance placed thereon.

Model		MI-1250	MI-1200	MI-1000	MI-900	MI-800
Input Parameters						
PV Module Compatibility		54-cell/108 half-cell, 60-cell/120 half-cell, 66-cell/132 half-cell and 72-cell/144 half-cell				
Min./Max. Input Voltage	U_{dcmin}/U_{dcmax} , V			16/60		
Peak Power Tracking Voltage Range	U_{mppmin}/U_{mppmax} , V	41 to 55	39 to 55	33 to 55	30 to 55	28 to 55
MPPT Voltage Range	U_{mppt} , V			16 to 60		
Nominal Input Voltage	U_{dcnom} , V			42		
Start-up Input Voltage	$U_{dcstart}$, V			22		
Max. Continuous Input Current	I_{dcmax} , A			20		
Max. Input Short-Circuit Current	I_{scmax} , A			25		
DC Port Overvoltage Class				II		
DC Port Backfeed Current	A			0		
Output Parameters						
Nominal Voltage	U_{acnom} , V			220/230/240		
Voltage Range	U_{acmin}/U_{acmax} , V			184 to 276		
Nominal Output Power	P_{acnom} , W	1250	1200	1000	900	800
Max. Apparent Power	S_{acmax} , VA	1250	1200	1000	900	800
Nominal Output Current @220Va.c.	I_{acnom} , A	5.68	5.45	4.55	4.09	3.64
Nominal Output Current @230Va.c.	I_{acnom} , A	5.43	5.22	4.35	3.91	3.48
Nominal Output Current @240Va.c.	I_{acnom} , A	5.21	5.00	4.17	3.75	3.64
Max. Output Current @220Va.c.	I_{acmax} , A	5.97	5.73	4.77	4.30	3.82
Max. Output Current @230Va.c.	I_{acmax} , A	5.71	5.48	4.57	4.11	3.65
Max. Output Current @240Va.c.	I_{acmax} , A	5.47	5.25	4.38	3.94	3.50
Max. Microinverters / 32A Branch Circuit -Three phase		15	15	18	21	21
Nominal Frequency	f_{nom} , Hz			50/60		
Extended Frequency Range	f_{min}/f_{max} , Hz			45 to 65		
Power Consumption at Night	mW			0 ^a		
AC Port Overvoltage Class				III		
Power Factor Setting	cosphi			>0.99		
Power Factor (Adjustable)				0.8 leading ... 0.8 lagging		
Total Harmonic Distortion	THDi			<1.5%		
AC Surge Protection				TYPE II		
Efficiency Parameters						
Peak Efficiency	η_{max} , %			98.2		
EU Efficiency	η_{EU} , %			97.5		
MPPT Efficiency	η_{MPPT} , %			99.9		
Mechanical Parameters						
Ambient Temperature Range	°C			-40 to 65		
Storage Temperature Range	°C			-40 to 85		
Relative Humidity Range	%			4 to 100, condensing		

a. The value is tested with M-Relay or M-Combiner.

Model		MI-1250	MI-1200	MI-1000	MI-900	MI-800
DC connector type				Stäubli MC4		
Number of DC connectors				2 pairs		
AC connector type				MT-02502-A ^b		
Number of AC connectors				1 pair		
Dimensions (without Bracket)	mm			250 × 202 × 35 (W x H x D)		
Weight (without Bracket)	kg			2.2		
Cooling				Natural convection		
Approved for Wet Locations				Yes		
Pollution Degree				III		
Topology				Isolated		
Enclosure Protection Class				Class II double-insulated		
Environmental Category				Outdoor - IP67		
Altitude	m			3000		
Noise	dB			<25		
Features						
Communication				PLC		
Indicator				1 × LED		
Compliance						
Safety				IEC 62109-1/-2		
EMC				IEC 61000-6-1/-2/-3/-4, EN 62920		
Grid Compliance				VDE 0124, VDE 4105, UTE 0126, EN 50549, EN 50530		

b. The AC connector must be used with M-Cables.